

Description

Gluecifer is a rapid curing polyurethane gel adhesive which can be applied by gun or straw.

Characteristic Composition	Standard	Classification Polyurethane Foam
Conformance	EN204/205	D4
Fire Class	EN 13501-1 DIN 4102-1	Class E B3
Open Time	3cm in width at 23°8 C and 50% RH	8 Minutes
Tack Free Time	3cm in width at 23°8 C and 50% RH	8 Minutes
Loading Time		24 hours
Peel Strength	209 - 263 Newtons	
Tensile Strength	10,500 KPa	
Application Temperature*		Canister: +10°c to + 30°c Ambient: 5°c to + 35°c
Service Temperature		Short Term: -40°c to + 130°c Long Term: - 40°c to + 90°c
Storage	Store in shaded, dry conditions between + 10°c and 25°c Store canister upright	
Life Span	12 months pallet 12-month shelf when stored as recommended in original unopened containers.	

Color Beige

Packaging 500 ml canisters (12 per box)

Excellent long-term resistance to seawater, limewater, dilute acids and caustic solutions

USE IN WELL VENTILATED SPACE and ensure all recommended protective equipment is worn during handling & use of this product. For full recommendation, refer to safety data sheet.

IMPORTANT: At least one surface should be porous.

- Always carry out a test to confirm compatibility prior to use.
- Remove all loose particles, dust and grease.
- Gluecifer is suitable for fixing grass to concrete, timber, some porcelain & aluminum edgings, grass tape, resin, tarmac paving, block pavers and much more (always carry out a test area first).
- For a speedier cure to be attained wetting the grass back and surface if needed.

Application Of Gluecifer Artificial Grass Glue

- Shake the canister vigorously at least 20 times or around 5 seconds.
- Remove the protective cap and screw onto your Gluecifer gun or straw.
- Apply around 3-5 beads and a zig-zag over a 100mm join.
- Keep the end of the nozzle just off the surface so as to keep clean at all times.
- For best results always work with the canister in a vertical position and keep the valve pointed downwards.
- ALWAYS clean the gun after each use with Gluecifer Heavenly Cleaner or if left for longer than 5 minutes. (Gun cleaning takes 3-5 seconds).

Coverage

A 500 ml canister of Gluecifer will deliver up to 107 linear metres of adhesive (based on a 10 mm wide bead).

Cleaning

Remove excess foam immediately with Gluecifer Heavenly Cleaner.

Ensure surface is solvent resistant before cleaning spillages.

Cured glue can only be removed mechanically.

Health & Safety Precautions

Safety data sheet must be read and understood before use.

Extremely flammable - keep away from open flames and other ignition sources.

Technical Service

Gluecifer strives to offer the best customer experience possible.

For help and assistance or more detailed information, service and advice,
please call Customer Services on +44 (0) 1435 83 11 44.

For EU Please call +31(0) 412 78 62 11

Guarantee / Warranty

Gluecifer products are manufactured to rigid standards of quality. Any product which has been
applied (a) in accordance with

Gluecifer written instructions and (b) in any application recommended by Gluecifer, but
which is proved to be defective, will be replaced free of charge.

No liability can be accepted for the information provided in this leaflet although it is published in good faith and
believed to be correct.

Gluecifer reserves the right to alter product specifications without prior notice, in line with Company policy of
continuous development and improvement.

Gluecifer

Unit 1

Squires Farm Industrial Estate

Palehouse Common

Franfield

East Sussex

TN22 5RB

sales@gluecifer.co.uk

www.gluecifer.co.uk

UK +44 (0) 1435 83 11 44.

EU +31(0) 412 78 62 11.